GreenPoint Rated Planning Scoresheet: Multifamily

The GreenPoint Rated checklist tracks green features incorporated into the home. GreenPoint Rated is provided as a public service by Build It Green, a professional non-profit whose mission is to promote healthy, energy and resource efficient buildings in California.

The minimum requirements for a GreenPoint Rated home are: Earn a total of 50 points or more; obtain the following minimum points per category: Community (6), Energy (30), Indoor Air Quality/Health (5), Resources (6), and Water (3); and meet the prerequisites A2a, E2a, H4a. (for 2008 permitted projects), J1a, N1. and Q0.

This checklist accommodates the verification of mandatory CALGreen measures but does not signify compliance unless accepted by jurisdictional authority. All CALGreen measures within the checklist must be selected as "Yes" or "n/a" for compliance with GreenPoint Rated. Build It Green is not a code enforcement agency.

The green building practices listed below are described in the GreenPoint Rated Multifamily Rating Manual. For more information please visit www.builditgreen.org/greenpointrated.

A home is only GreenPoint Rated if all features are verified by a Certified GreenPoint Rater through Build It



Total Points Targeted:

Green.	reem ont reaction an reactives are vermed by a certified creem ont reactiniough build it		8		5	6 6	3							
Multifamily New I	Home 2.2 / 2008 Title 24													
The Res	sidences at California Center	þe							ation	ion	Ē			
	Pete Kennedy	Targeted	t		ے	ဟ		Ş	Rough Verific	Final Verification	cumentation			
	3685	Tar	ommunity	_	AQ/Health	Resources		Plan Review	Ve.	erif	ent			
		nts	m m	Energy	¥	nos	Water	ر چ	lgh	<u></u>	ün			
Plannin	g Scoresheet	Points	CO	En	IAG	Re	Na	Plaı	Rol	Fin	Doc			
AA. COMMUNIT	Y DESIGN AND PLANNING		Points Available per Measure						re R=recomm A=alteri					
	1. Develop Infill Sites													
No	a. Project is an Urban Infill Development		1								R			
36	 b. Conserve Resources by Increasing Density -15 Units Per Acre or Greater (1 Point for every additional 5 dwelling units/acre) Enter Project Density Number (In du/acre) 	5	10					R			Α			
No	c. Project Includes the Redevelopment of At Least One Existing Building					1		Α	Α		Α			
TBD	d. Build on Designated Brownfield Site or City-Designated Redevelopment Area		1						Α		R			
	2. Design for Walking & Bicycling													
TBD	a. Sidewalks Are Buffered from Roadways & Are 5 Feet Wide (8 Feet in Retail Areas)		1					Α		Α				
TBD	b. Install Traffic Calming Strategies		1					Α		Α				
Yes	c. Provide Dedicated, Covered & Secure Bicycle Storage for 15% of Residents	1	1					Α		Α				
Yes	 d. Provide Secure Bicycle Storage for 5% of Non-Residential Tenant Employees & Visitors 	1	1					Α		Α	Α			
	3. Alternative Transportation													

The Res	sidences at California Center Pete Kennedy	Points Targeted	ty		ے	v		Wé	Rough Verification	Final Verification	Documentation
	3685	Tar	nuni	_ ≥	ealt	lrce		evie	Nei	/erif	nent
Plannin	g Scoresheet	oints	Community	Energy	AQ/Health	Resources	Water	Plan Review	ong	nal \	ocun
I Idillilli	a. Site Has Pedestrian Access Within ½ Mile of Community Services:	ď	O	Ш		<u> </u>	S	正	Ř	证	Ŏ
7	TIER 1: Enter number of services within ½ Mile: 1) Day Care 2) Community Center 3) Public Park 4) Drug Store 5) Restaurant 6) School 7) Library 8) Farmer's Market 9) After School Programs 10) Convenience Store Where Meat & Produce are Sold										
11	TIER 2: Enter number of services within ½ Mile: 1) Bank 2) Place of Worship 3) Laundry/Cleaners 4) Hardware 5) Theater/Entertainment 6) Fitness/Gym 7) Post Office 8) Senior Care Facility 9) Medical/Dental 10) Hair Care 11) Commercial Office or Major Employer 12) Full Scale Supermarket										
	i. 5 Services Listed Above (Tier 2 Services Count as 1/2 Service Value)	1	1							Α	R
	ii.10 Services Listed Above (Tier 2 Services Count as 1/2 Service Value)	1	1							Α	R
	b. Proximity to Public Transit: Development is Located Within			1	1	1	1				
Yes	i. 1/4 Mile of One Planned or Current Bus Line Stop	1	1							Α	A
Yes	ii. 1/2 Mile of a Major Transit Stop (Commuter Train/Light Rail Transit System OR Two or More Planned/Current Bus Line Stops	1	1							Α	A
TBD	c. Reduced Parking Capacity i. Less than 1.5 Parking Spaces Per Unit		1					A			Α
No	ii. Less than 1.0 Parking Spaces Per Unit		1					A			A
NO	4. Mixed-Use Developments							<u> </u>			
	a. At least 2% of Development Floor Space Supports Mixed-Use (Non-Residential									_	
Yes	Tenants)	1	1					R		R	
TBD	b. Half of the Non-Residential Floor Space is Dedicated to Community Services (See AA3a)		1								R
	5. Outdoor Gathering Places										
Yes	a. Private or Semi-Public Outdoor Gathering Places for Residents (Minimum of 50 sf Per Unit) (mutually exclusive with AA5b)	1	1					R		R	
Yes	 b. Outdoor Gathering Place of Compact Site Provides Natural Elements (mutually exclusive with AA5a) (Projects Must Be a Minimum of 50 du/acre) 		1					R		Α	
Yes	c. Public Outdoor Gathering Places have Direct Access to At Least Two Tier 1 Community Services (See AA3a)	1	1					R		Α	
	6. Design for Safety and Vandalism Deterrence										
Yes	a. Residence Entries Have Views to Callers (Windows or Double Peep Holes) & Can Be Seen By Neighbors	1	1							R	
Yes	b. All Main Entrances to the Building and Site are Prominent and Visible from the Street	1	1							R	
© Build	7. Passive Solar Design It Green GreenPoint Rated Multifamily New Home Data Collection	n Form	v1.9/	2/2					Page 2	of 14	

	esidences at California Center Pete Kennedy 3685 ng Scoresheet	Points Targeted	Community	Energy	AQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
No				2		<u> </u>	>	R	<u>«</u>	R	A
INU	a. Provide Appropriate Orientation for Maximum Energy Efficiency b. Provide Appropriate Shading On All South-Facing Windows for Effective Passive							K		K	_A_
No	Solar Control			1				R		R	Α
No	c. Provide Thermal Mass			2				R		R	Α
	8. Adaptable Buildings										
	a. Include Universal Design Principles in Units										
TBD	i. 50% of Units		1					R	R	R	
TBD	ii. 80% of Units		1					R	R	R	
No	b. Live/Work Units Include A Dedicated Commercial Entrance		1					R		R	
	9. Affordability										
	a. Units are Dedicated to Households Making 80% or Less of AMI										
TBD	i. 10% of All Units		1								R
No	ii. 25%		1				-				R
No	iii. 50% or More		1								R
TBD	b. Development Includes Multiple Bedroom Units (Minimum of 2 3-Bdrm Units At or Less Than 80% AMI)		1					R			R
No	c. At least 20% of Units at 120% or Less of AMI are For-Sale		1				-	R			R
INU	Total Available Points in Community Design and Planning: 42	16	'					_ K			K
A. SITE	Total Available Forms in Community Design and Flaming. 42	10	Poi	nts Ava	ilable p	er Mea	sure				
741 011 2	1. Protect Topsoil and Minimize Disruption of Existing Plants & Trees				Р	0					
TBD	a. Protect Topsoil and Reuse After Construction		1			1		R	R	R	R
TBD	b. Limit and Delineate Construction Footprint for Maximum Protection		· ·			1		R	R	R	R
100	2. Divert/Recycle Job Site Construction Waste (Including Green Waste						<u> </u>				
	and Existing Structures)										
	a. Required: Divert 50% (by weight) of All Construction & Demolition Waste										
Yes	(Recycling or Reuse) (CALGreen code)	Y				R					R
TBD	b. Divert 100% of Asphalt and Concrete and 65% (by weight) of Remaining Materials					2					R
TBD	c. Divert 100% of Asphalt and Concrete and 80% (by weight) of Remaining Materials					2					R
	3. Construction Environmental Quality Management Plan, Duct Sealing,										
	and Pre-Occupancy Flush-Out										
	[*This credit is a requirement associated with PJ1: EPA IAP]										
Yes	a. Duct openings and other related air distribution component openings shall be covered	1			1			R	R	R	R
100	during construction. (CALGreen code if applicable)	·									.,
TBD	b. Full environmental quality management plan and pre-occupancy flush out is conducted (Prerequisite is A5a)				1			R		R	R
Yes	4. Use Recycled Content Aggregate (Minimum 25%)	1				1			Α		R
TBD	5. Cool Site: Reduce Heat Island Effect on Site		1					R		R	
	Total Available Points in Site: 11	2									
B. LANDSCAP			Poi	nts Ava	ilable p	er Mea	sure				
© Buile	d If Green Green Point Rated Multifamily New Home Data Collection	n Form	v1.9/	2/2				<u> </u>	Page :	3 of 1	4

	sidences at California Center Pete Kennedy 3685 ng Scoresheet	Points Targeted	Community	Energy	IAQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
25.0%	Is the landscape ≥ 10% of the site area? Sites with less than 10% of the total site area dedicated to landscaping can only earn up to 4 points for measures B1a through B1g. Calculate the landscape area percentage by dividing the landscape area by the total site area. Include the building footprint(s) and all other developed portions of the site up to the site boundary.										
TBD	a. Group Plants by Water Needs (Hydrozoning)						2				R
Yes	b. Mulch All Planting Beds to the Greater of 3 Inches or Local Water Ordinance Requirement	2					2			R	
Vaa	c. Construct Resource-Efficient Landscapes i. No Invasive Species Listed by Cal-IPC Are Planted	1				- 4		<u> </u>			R
Yes TBD	ii. No Plant Species will Require Shearing	1				1					R
Yes	iii. 75% of Plants are Drought-tolerant, California Natives, Mediterranean or Other Appropriate Species	3					3				R
	d. Minimize Turf in Landscape Installed by Builder										
TBD	i. Turf Shall Not Be Installed on Slopes Exceeding 10% and No Overhead Sprinklers Installed in Areas Less than 8 Feet Wide						2	А		Α	А
Yes	ii. Turf Is ≤ 33% of Landscaped Area	2					2	Α		Α	Α
	e. Install High-Efficiency Irrigation Systems										
Yes	i. System Uses Only Low-Flow Drip, Bubblers or Sprinklers	2					2			Α	Α
Yes	ii. System Has Smart (Weather-based) Controller (CALGreen code if applicable)	3					3			Α	Α
TBD	f. Incorporate Two Inches of Compost in the Top 6 to 12 Inches of Soil g. Design Landscape to Meet Water Budget						3				R
Yes	i. Install Irrigation System That Will Be Operated at <70% Reference ET (B1a. and B1b. are Prerequisites for Credit)						1				R
TBD	ii. Install Irrigation System That Will Be Operated at <50% Reference ET (B1a., B1b. and B1ei. or B1eii. are Prerequisites for Credit)						1				R
No	h. Incorporate Community Garden		1					\vdash		R	R
Na	2. Source Water Efficiency							<u> </u>	Б		-
No No	a. Use Recycled Water for Indoor and/or Outdoor Water Use						2	\vdash	R	Α.	R
INU	b. Use Rainwater for Indoor and/or Outdoor Water Use 3. Outdoor Play Structures and Outdoor Furniture						4		A	Α	R
TBD	a. Play Structures and Outdoor Furniture a. Play Structures & Surfaces Have an Average Recycled Content ≥20%					1				Α	R
TBD	b. Environmentally Preferable Exterior Site Furnishings					1				A	R
TBD	4. Reduce Light Pollution by Shielding Fixtures and Directing Light Downward		1							A	A
	Total Available Points in Landscape: 33	13		·							
C. DESIGN CO	NSIDERATIONS		Poi	nts Ava	ilable p	er Mea	sure				
© Build	1. Acoustics: Noise and Vibration Control It ആല്യസ് 2 points for credit, includ@geeন അന്റ്റ് സുക്കാരി സ്വാദ്യം വിദ്യാം വിദ്യാ	n Form	v1.9/	 2/2					Page 4	4 of 1	4

Yes	Water Plan Review	Rough Verification	Final Verification	Documentation
Yes 3) Airborne and Structure-borne Noise Reduction (e.g., walls, floor-ceilings) 1		Α	Α	R
TBD 4) Mechanical Ventilation Noise and Vibration Control 5) Plumbing Noise and Vibration Reduction		A	Α	R
TBD TIER 2: 1) Minimize Stair Impact Noise 1 0.5		A	Α	R
TBD TIER 2: 1) Minimize Stair Impact Noise 2) Minimize Trash Chute Noise 4) Mixed-Use Noise and Vibration Reduction 2. Mixed-Use Noise and Vibration Reduction 2. Mixed-Use Dosign Strategies TBD a. Develop Green Tenant Improvement Requirements for Build Outs b. Commercial Loading Area Separated from Residential area c. Separate Mechanical and Plumbing Systems 3. Commissioning TBD a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Stag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for lowrise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	+	A	A	R
TBD 2) Minimize Floor Squeaks 3) Minimize Trash Chute Noise 4) Mixed-Use Noise and Vibration Reduction 0.5	+	A	A	R
TBD 3) Minimize Trash Chute Noise 4) Mixed-Use Noise and Vibration Reduction 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5		A	A	A
TBD 4) Mixed-Use Noise and Vibration Reduction 2. Mixed-Use Design Strategies a. Develop Green Tenant Improvement Requirements for Build Outs BD b. Commercial Loading Area Separated from Residential area c. Separate Mechanical and Plumbing Systems 3. Commissioning a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	+	A	A	A R
2. Mixed-Use Design Strategies a. Develop Green Tenant Improvement Requirements for Build Outs b. Commercial Loading Area Separated from Residential area c. Separate Mechanical and Plumbing Systems d. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) Slag (Minimum 20%) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) TBD i. Sudd at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1 1		A	A	R
TBD a. Develop Green Tenant Improvement Requirements for Build Outs b. Commercial Loading Area Separated from Residential area c. Separate Mechanical and Plumbing Systems 3. Commissioning a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for lowrise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 2		A	A	<u> </u>
TBD b. Commercial Loading Area Separated from Residential area c. Separate Mechanical and Plumbing Systems 3. Commissioning a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) TBD b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	_			R
TBD c. Separate Mechanical and Plumbing Systems 3. Commissioning a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	R	Α	Α	IX
3. Commissioning a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 2. D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	R	A	A	_
a. Design Phase (Define Owner's Project Requirements, Basis of Design, and Develop Plan) b. Construction Phase (Perform Functional Testing) c. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' 		- / (
C. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load				R
C. Post-Construction Phase (Verify Compliance, Commissioning Report, Training and Warranty Review) Total Available Points in Design Considerations: 14 D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load				R
D. FOUNDATION, STRUCTURAL FRAME & BUILDING ENVELOPE TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load Points Available per Mea				R
TBD 1. Replace Portland Cement in Concrete with Recycled Fly Ash and/or Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 3 3 3 4 5 6 7 7 7 8 8 9 9 1 1 1 1 1 1 1 1 1 1 1				
Slag (Minimum 20%) TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1	asure			
TBD 2. Design, Build and Maintain Structural Pest and Rot Controls (for low-rise projects) 3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1 1 1 1 1 1 1 1 1 1 1 1				R
TBD TBD a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	+	+	+	
3. Construction Material Efficiencies a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1 1 1		R		
a. Wall and Floor Assemblies (excluding solid wall assemblies) are Delivered Panelized from Supplier (Minimum of 80% square feet) b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
b. Modular Components are Delivered Assembled to the Project (Minimum 25%) c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 5 6 6 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		R		R
c. Optimal Value Engineering i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor ii. Door & Window Headers Sized for Load 1 1		R		R
TBD i. Studs at 24 Inch on Center at Interior Non-Bearing Walls and Top Floor Yes ii. Door & Window Headers Sized for Load 1 1				
Yes ii. Door & Window Headers Sized for Load 1 1		R		\Box
		R		
		R		
4. Use Engineered Lumber				
TBD a. Engineered Beams and Headers	$\overline{}$	R	T	\Box
TBD b. Wood I-Joists or Web Trusses for Floors		R		
TBD c. Engineered Lumber for Roof Rafters		R		
TBD d. Engineered or Finger-Jointed Studs for Vertical Applications		R		
TB® Build It & Perinted Strand Board for SubflogreenPoint Rated Multifamily New Home Data Collection Form v1.9/2/2		_	5 of 1	1

The Residences at California Center Pete Kennedy	Points Targeted	r,		_	(0		>	Rough Verification	Final Verification	Documentation
3685	Taré	Community		AQ/Health	Resources		Plan Review	Ver	erifi	ent
	nts	E E	Energy) ¥	nos	Water	n R	y gr	a <	mn:
Planning Scoresheet	Poi	ပိ	Ë	<u> </u>	Re Re	Na	Pla	Rol	Ein	Дос
TBD f. Oriented Strand Board for Wall and Roof Sheathing					1			R		
TBD 5. Insulated Headers			1					R		
6. Use FSC-Certified Wood										
TBD a. Dimensional Lumber, Studs and Timber (Minimum 40%)					4			Α		R
TBD b. Panel Products (Minimum 40%)					2			Α		R
7. Energy Heels on Roof Trusses for Low-Rise Projects			1				Α	Α		
8. Use Solid Wall Systems (Includes SIPS, ICFs, & Any Non-Stick Frame										
Assembly) TBD a. Floors					2		_	Α		
TBD a. Floors TBD b. Walls					2		A	Α		
TBD b. Walls c. Roofs					2		A	A		
Total Available Points in Foundation, Structural Frame & Building Envelope: 34	1						_ A	А		
E. EXTERIOR	-	Poir	nts Ava	ilahle n	er Mea	SUITE				
1. Drainage Planes and Durable Siding		Points Available per Measure								
No a. Install a Rain Screen Wall System					2		Α	R		
Yes b. Use Durable and Non-Combustible Siding Materials	1				1		A		Α	A
2. Durable Roofing Options										
a. Required: All Roofing Has 3-Year Subcontractor Warranty and a 20-Year Manufacturer Warranty	Υ				R					R
Yes b. Use Durable and Fire Resistant Roofing Materials or Assembly	1				1				R	R
No 3. Vegetated Roof (2 points for 25%, 4 points for 50%)		4					R		R	
Total Available Points in Exterior: 8	2									
F. INSULATION		Poir	nts Ava	ilable p	er Mea	sure				
1. Install Insulation with 75% Recycled Content										
TBD a. Walls					1			Α		Α
TBD b. Ceilings					1			Α		A
TBD c. Floors					1		\vdash	Α		A
Total Available Points in Insulation: 3		D :	ι Δ		B.4					
G. PLUMBING		Poli	its Ava	ilable p	er iviea	sure				
 Water Efficient Fixtures a. Install High Efficiency Toilets (Dual Flush or ≤ 1.28 Gallons Per Flush (gpf)) (CALGreen code 										
if applicable)										
Yes i. In All Residences	1.84					1.84			R	R
Yes ii. In All Non-Residential Areas	0.16					0.16			R	R
b. High Efficiency Urinals or No-Water Urinals Are Specified:										
Yes i. Average Flush Rate is ≤0.5 gpf (CALGreen code if applicable)	1					1			R	R
No ii. Average Flush Rate is ≤0.1 gpf						1			R	R
a High Efficiency Chayarhanda Hag < 2.0 Callana Dar Minuta (apm) at 90 nai (CAI Crean and	2					2			Р	P
Yes © Build It ੴReelicable) GreenPoint Rated Multifamily New Home Data Collection	n Form	v1.9/2	2/2			3		Page (6 of 14	R 4

The Re	sidences at California Center	ted							Rough Verification	tion	on
	Pete Kennedy	arge	nity		윺	s S		iew	erifi	ifica	ntati
	3685	S T	ommunity	<u>8</u>	Hea) arc	_	Rev	٦ >	Ver	IJ EI
Plannir	ng Scoresheet	Points Targeted	Com	Energy	IAQ/Health	Resources	Water	Plan Review	Roug	Final Verification	Documentation
	d. Flow Limiters Or Flow Control Valves Are Installed on All Faucets										
Yes	i. Residences: Kitchen - ≤ 1.8 gpm (CALGreen code if applicable)	0.92					0.92			R	R
Yes	ii. Non-Residential Areas: Kitchen - ≤ 1.8 gpm (CALGreen code if applicable)	0.08					0.08			R	R
Yes	iii. Residences: Bathroom Faucets- ≤ 1.5 gpm at 60psi	1					1			R	R
Yes	iv. Non-Residential Areas: Bath Faucets - ≤ .5 gpm or .25 gal for meter faucets (CALGreen code if applicable)	Υ					0			R	R
	2. Distribute Domestic Hot Water Efficiently (G2a is a Prerequisite for credit										
	for G2 b-e. Maximum 5 Points) a. Insulate All Hot Water Pipes										
TBD	[*This credit is a requirement associated with PJ1: EPA IAP]			1			1		R		
TBD	b. Use Engineered Parallel Plumbing						1	Α	Α		
TBD	c. Use Engineered Parallel Plumbing with Demand Controlled Circulation Loop(s)						1	Α	Α		
	d. Use Traditional Trunk, Branch and Twig Plumbing with Demand Controlled							_			
TBD	Circulation Loop(s)			1			2	Α	Α		
TBD	e. Use Central Core Plumbing			1		1	1	Α	Α		
TBD	3. Water Submetering: Bill Tenants for Actual Usage						4		Α	Α	
	Total Available Points in Plumbing: 18	8									
H. Heating Ven	tilation and Air Conditioning		Poii	nts Ava	ilable p	er Mea	sure				
TBD	1. Install High Performing Zoned Radiant Hydronic Heating				2			Α	Α		
TBD	2. Install High Efficiency Air Conditioning with Environmentally Preferable		1							Α	Α
	Refrigerants										
	3. Advanced Ventilation Practices for Cooling										
TBD	a. Operable Windows or Skylights Are Placed To Induce Cross Ventilation In At Least One Room In 80% of Units			1	1			Α		Α	
	-										
TBD	b. Mechanical Ventilation System for Cooling: i. ENERGY STAR Ceiling Fans and Light Kits in Living Areas & All Bedrooms			1						R	Α
TBD	ii. Whole House Fan (CALGreen code if applicable)			1						R	
	4. Advanced Mechanical Ventilation for IAQ			1						- 11	
	a. Required: Compliance with ASHRAE 62.2 Mechanical Ventilation Standard (As										
Yes	Adopted in Title 24 Part 6) N/A for projects permitted under 2005 Title 24.	Y			R				Α	Α	R
TDD	b. Advanced Ventilation Practices (Continuous Operation, Sone Limit, Minimum				4					_	
TBD	Efficiency, Minimum Ventilation Rate, Homeowner Instructions)				1				Α	Α	R
Yes	c. Outdoor Air Ducted to Bedroom and Living Areas of Home	2			2			R	Α	Α	
TBD	d. ENERGY STAR Bathroom Fans on Timer or Humidistat (CALGreen code if applicable)				1					R	R
	5. Garage Ventilation Fans Are Controlled by Carbon Monoxide Sensors										
Yes	(Passive Ventilation Not Eligible)	1			1			R		R	R
	[*This credit is a requirement associated with PJ1: EPA IAP]										

	esidences at California Center Pete Kennedy 3685	Points Targeted	Community	Energy	AQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
Plannii	ng Scoresheet	Poi	ပိ	Ë	₽	Se l	×	Pla	Rot	Ein	Doc
Yes	6. Install Carbon Monoxide Alarms (or No Combustion Appliances in Living Space and No Attached Garage) [*This credit is a requirement associated with PJ1: EPA IAP]	1			1					R	
L DENEWARD	Total Available Points in Heating Ventilation and Air Conditioning: 13	4	Dei	- 1 - A	:1 - 1 - 1 - · ·	N A					
I. RENEWABL			Poli	nts Ava	ilable p	er Mea	sure				
No	1. Solar Hot Water System Preheats Domestic Hot Water			4				R		R	
No No No	2. Offset a Percentage of the Project's Estimated Electricity Demand with Onsite Renewable Generation a. 60% of Common Area Load b. 90% of Common Area Load c. 10% or More of Residential Units Load		2 2 2	2 2 2							R R R
110	Total Available Points in Renewable Energy: 16							\vdash			
J. BUILDING F	PERFORMANCE		Poi	nts Ava	ilable p	er Mea	sure				
	1. Building Performance Exceeds Title 24										
	Enter the Percent Better Than Title 24 for Residential and Non-Residential Portions of the										
15.0%	Project. a. Required: Residences: Minimum 15% Better Than Title 24. 2 Points for Every 1% Better Than Title 24	30		30+				R			
	b. Non-Residential Spaces: 1 Point for Every 1% Better Than Title 24, adjusted for square footage			1+				R			
	2. Building Envelope Diagnostic Evaluations										
TBD	a. Duct Testing Results in Leakage < 6% [*This credit is a requirement associated with PJ1: EPA IAP]			1							R
TBD	b. Blower Door Testing Results for Air Change per Hour is < 3.5 ACH ₅₀ [*This credit is a requirement associated with PJ1: EPA IAP]			2							R
TBD	c. Verify Quality of Insulation Installation & Thermal Bypass Checklist before Drywall [*This credit is a requirement associated with PJ1: EPA IAP]			1							R
No	3. Design and Build Near Zero Energy Homes (Enter number of points, minimum of 2 and maximum of 6 points)			6						Α	R
Yes	4. Title 24 Prepared and Signed by a CABEC Certified Energy Plans Examiner (CEPE)	1		1				R			Α
	5. Participation in Utility Program with Third Party Plan Review										
Yes	a. Energy Efficiency Program [*This credit is a requirement associated with PJ1: EPA IAP]	1		1				Α			R
TBD	b. Renewable Energy Program with Min. 30% Better Than Title 24 (High Performing Home)			1				Α			R
	Total Available Points in Building Performance: 43+	32									
K. FINISHES			Poi	nts Ava	ilable p	er Mea	sure				
⊜ D:I	1. Entryways			2 /2					Dogo		

The Residences at California Center	70							tion	r.	
Pete Kennedy	Points Targeted	>					>	Rough Verification	Final Verification	Documentation
3685	Tarć	Community		IAQ/Health	Resources		Plan Review	Veri	erifi	enta
	nts	E E	Energy	 }H€	nos	Water	ر 8	lgh	<u>~</u>	E II
Planning Scoresheet	Poi	ပိ	E	IAG	Re e	%	Plaı	Rou	Fin	Doc
TBD a. Design Entryways to Reduce Tracked-In Contaminants for All Home Entrances				1					R	
b. Permanent Walk-Off Systems Are Provided at All Main Building Entrances & In				1					R	
Common Areas				'	4					_
TBD 2. Use Recycled Content Paint 3. Low/No-VOC Paints & Coatings					1		-		Α	R
[*This credit is a requirement associated with PJ1: EPA IAP]										
 a. Low-VOC Interior Wall/Ceiling Paints (<50 grams per liter (gpl) VOCs Regardless of Sheen) (CALGreen code if applicable) 										
Yes i. In All Residences	0.92			0.92					Α	R
TBD ii. In All Non-Residential Areas				0.08					Α	R
b. Zero-VOC: Interior Wall/Ceiling Paints (<5 gpl Regardless of Sheen)										
No i. In All Residences				0.92					Α	R
No ii. In All Non-Residential Areas				0.08					Α	R
c. Use Low-VOC Coatings That Meet SCAQMD Rule 1113 (CALGreen code if applicable)										
Yes i. In All Residences	1.84			1.84					Α	R
N/A ii. In All Non-Residential Areas				0.16					Α	R
4. Use Low VOC Caulks, Construction Adhesives and Sealants that Meet	1			1			R	R		R
SCAQMD Rule 1168 (CALGreen code if applicable)				<u> </u>			L.,			
5. Environmentally Preferable Materials for Interior Finish:										
A) FSC-Certified Wood, B) Reclaimed Lumber, C) Rapidly Renewable, D) Recycled-										
Content, E) Finger-Jointed, or F) Local a. Residences: At Least 50% of Each Material:										
TBD i. Cabinets			T		3.69				Α	Α
TBD ii. Interior Trim					1.84				A	A
TBD iii. Shelving					1.84				A	A
TBD iv. Doors					1.84				A	Α
TBD v. Countertops					1.84				A	Α
b. Non-Residential Areas: At Least 50% of Each Material:				1						
TBD i. Cabinets					0.31				Α	Α
TBD ii. Interior Trim					0.16				Α	Α
TBD iii. Shelving					0.16				Α	Α
TBD iv. Doors					0.16				Α	Α
TBD v. Countertops					0.16				Α	Α

	esidences at California Center Pete Kennedy 3685 ng Scoresheet	Points Targeted	Community	Energy	IAQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
Yes	6. Reduce Formaldehyde in Interior Finish – Meet Current CARB Airborne Toxic Control Measure (ATCM) for Composite Wood Formaldehyde Limits by Mandatory Compliance Dates (CALGreen code if applicable) [*This credit is a requirement associated with PJ1: EPA IAP]	Y				0		A		Α	R
	7. Reduce Formaldehyde in Interior Finish - Exceed Current CARB ATCM for Composite Wood Formaldehyde Limits Prior to Mandatory Compliance Dates a. Residences: At Least 90% of Each Material:										
TBD	i. Doors				0.92				Α	Α	Α
TBD	ii. Cabinets and Countertops				1.84					A	A
TBD	iii. Interior Trim and Shelving b. Non-Residential Areas: At Least 90% of Each Material				0.92			_		Α	A
TBD	i. Doors				0.08				Α	Α	Α
TBD	ii. Cabinets and Countertops				0.16				_	A	A
TBD	iii. Interior Trim and Shelving				0.08					A	A
	8. Durable Cabinets				0.00						
TBD	a. Residences					0.92		R		R	
TBD	b. Non-Residential Areas					0.08		R		R	
TBD	9. At Least 25% of All Newly Supplied Interior Furniture has					1				Ъ	В
IBD	Environmentally Preferable Attributes					'				R	R
	Total Available Points in Finishes: 26	4									
L. FLOORING			Poii	nts Ava	ilable p	er Mea	sure				
	 1. Use Environmentally Preferable Flooring (Minimum 15% of Floor Area) A) FSC-Certified Wood, B) Reclaimed or Refinished, C) Rapidly Renewable, D) Recycled-Content, E) Exposed Concrete, or F) Local. Flooring Adhesives Must Meet SCAQMD Rule 1168 for VOCs 										
TBD	a. Residences					3.69				Α	Α
TBD	b. Non-Residential Areas					0.31				Α	Α
	2. Low-Emitting Flooring										
	[*This credit is a requirement associated with PJ1: EPA IAP]										
TBD	a. Residences: Low Emitting Flooring (50% Minimum) (Section 01350, CRI Green Label Plus, Floorscore)				1.84			Α		R	R
TBD	b. Non-Residential Areas: Low-Emitting Flooring (50% Minimum) (Section 01350, CRI Green Label Plus, Floorscore)				0.16			Α		R	R
Yes	3. All carpet and 50% of Resilient Flooring is low emitting. (CALGreen code if applicable)	Υ			0					R	R
	Total Available Points in Flooring: 6										
M. APPLIANC	ES & LIGHTING		Poi	nts Ava	ilable p	er Mea	sure				
@ Buil	d It Green GreenPoint Rated Multifamily New Home Data Collection	n Form	v1 Q/	2/2				P	age 10) of 1	1

	sidences at California Center Pete Kennedy 3685 Ig Scoresheet	Points Targeted	Community	Energy	AQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
1 Idillilli		ď	0	ш		<u> </u>	>	죠	Ř	证	Ď
Yes	ENERGY STAR Appliances a. Install ENERGY STAR Dishwasher (Must Meet Current Specifications)	2		1			1			R	R
103	b. install ENERGY STAR Clothes Washer			1			'	_		- 1	
TDD	i. Meets ENERGY STAR and CEE Tier 2 Requirements			,						_	
TBD	(Modified Energy Factor ≥2.0; Water Factor ≤6.0) (Total 3 Points)			1			2			R	R
TBD	ii Meets ENERGY STAR and CEE Tier 3 Requirements						2			R	R
100	(Modified Energy Factor ≥2.2; Water Factor ≤4.5) (Total 5 Points)										
TDD	c. Install ENERGY STAR Refrigerators in All Locations							<u> </u>		_	
TBD	i. ENERGY STAR-Qualified & < 25 Cubic Feet Capacity			1						R	R
TBD TBD	ii. ENERGY STAR-Qualified & < 20 Cubic Feet Capacity 2. Common Laundry Facilities Are Provided for All Occupants			1		- 4		_	Α	R	R
TBD	Provide Built-In Recycling Center In Each Residential Unit					1		_ A	A	A R	-
100	4. Low-Mercury Lamps							\vdash		K	
)							<u> </u>			
TBD	a. Low-Mercury Products Are Installed Wherever Linear Fluorescent Lamps Are Used or Replaced					1				R	R
TBD	b. Low-Mercury Products Are Installed Wherever Compact Fluorescent Lamps Are Used or Replaced					1				R	R
	5. Install High-Efficacy Lighting and Design Lighting System										
TBD	a. Install High-Efficacy Lighting			1				Α		R	R
TBD	b. Install a Lighting System to IESNA Footcandle Standards or Hire Lighting Consultant			1				Α		Α	R
Yes	6. Gearless Elevators Are Installed	1		1				R		Α	Α
	Total Available Points in Appliances & Lighting: 16	3									
N. OTHER			Poir	nts Ava	ilable p	er Mea	sure				
Yes	Required: Incorporate GreenPoint Rated Checklist in Blueprints [*This credit is a requirement associated with PJ1: EPA IAP]	Y	R					R			
Yes	2. Pre-Construction Kick-Off Meeting with Rater and Subs	1	1								R
	3. Operations & Maintenance Manuals and Training										
Vac	[*This credit is a requirement associated with PJ1: EPA IAP]	1		4				<u> </u>			D
Yes TBD	a. Provide O&M Manual to Building Maintenance Staff (CALGreen code if applicable) b. Provide O&M Manual to Occupants and Orientation	1		1			1	-			R
TBD	Provide Oaki Manual to Occupants and Orientation Residents Are Offered Free or Discounted Transit Passes		2					\vdash			R
TBD	5. Educational Signage of Project's Green Features		1					\vdash		R	11
TBD	6. Install Home/Building System Monitor(s)			1				-		R	R
TBD	7. Use Vandalism Deterrence Practices and Develop Vandalism Management Plan		1								R
	Total Available Points in Other: 9	2									
O. (Not Used)											
@ Dil	Croop Point Poted Multifornily New Home Data Collection		4 0 //	2/0					000 1	4 . (4	4

The Re	sidences at California Center	pe							Rough Verification	ion	ň
	Pete Kennedy	Points Targeted	<u>₹</u>		ے	ဖွ		M	rific	Final Verification	Documentation
	3685	Tar	ommunity	>	AQ/Health	Resources		Plan Review	Ve.	erif	nent
Diami		nts	Ĕ	Energy) Ř	nos	Water	Z.	y gr	<u>a</u> <	Sum
Plannii	ng Scoresheet	Poi	ပိ	п	ĕ	Re	×	Pla	Rol	Fiin	Doc
D INDIONATIO	NO.		Dei	- 4 - A		N/					
P. INNOVATIO	A. Site		Poli	nts Ava	iiabie p	er iviea	sure				
	Stormwater Control: Prescriptive Path (Maximum of 3 Points, Mutually Exclusive With										
	PA2)										
TBD	a. Use Permeable Paving for 25% of Driveways, Patios and Walkways		1					Α	Α	Α	
Yes	b. Install Bio-Retention and Filtration Features	2	2					Α	Α	Α	
TBD	c. Route Downspout Through Permeable Landscape		1					Α	Α	Α	
TBD	d. Use Non-Leaching Roofing Materials		1					Α	Α	Α	
TBD	e. Include Smart Street/Driveway Design		1					Α	Α	Α	
	2. Stormwater Control: Performance Path (Mutually Exclusive With PA1):										
TBD	Perform a Soil Percolation Test and Capture and Treat 85% of Total Annual Runoff		3								R
	D. Foundation, Structural Frame and Building Envelope										
TBD	1. Use Radon Resistant Construction				2			A	Α		
	[*This credit is a requirement associated with PJ1: EPA IAP]				_						
TBD	2. Install a Foundation Drainage System					2		Α	R		R
	[*This credit is a requirement associated with PJ1: EPA IAP] 3. Moisture Controlled Crawlspace										_
TBD	[*For projects with crawlspaces, this credit is a requirement associated with PJ1: EPA				2					R	
100	IAP]				_					'`	
	E. Exterior										
TDD	1. Flashing Installation Techniques Specified and Third-Party Verified					1			_		
TBD	[*This credit is a requirement associated with PJ1: EPA IAP]					1		R	R		
	H. Heating Ventilation and Air Conditioning										
	1. Design and Install HVAC System to ACCA Manual J, D, and S Recommendations (CALGreen										
Yes	code if applicable) [*This credit is a requirement associated with PJ1: EPA IAP]	4		4					R		R
TBD	2. Pressure Relieve the Ductwork System (Mutually exclusive with H1) [*For projects with			1					R		
100	ducted systems, this credit is a requirement associated with PJ1: EPA IAP]										
TDD	3. Install High Efficiency HVAC Filter (MERV 6+, Mutually exclusive with H1.)										
TBD	[*This credit is a requirement associated with PJ1: EPA IAP]			1						R	
	J. Building Performance										
TBD	Obtain EPA Indoor airPlus Certification			2							R
	(Total 39 possible points, not including Title 24 performance; read comment)										
TBD	2. Third-Party Testing of Mechanical Ventilation Rates for IAQ (Meet ASHRAE 62.2)				2				Α	Α	
	[*This credit is a requirement associated with PJ1: EPA IAP]			4							
TBD	3. ENERGY STAR New Homes: High-Rise Pilot Program			1							R
	K. Finishes										

	esidences at California Center Pete Kennedy 3685 ng Scoresheet	Points Targeted	Community	Energy	IAQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation		
Yes	Use Moisture Resistant Material in Wet Areas: Kitchens, Bathrooms, Utility Rooms and Basements [*This credit is a requirement associated with PJ1: EPA IAP]	2			1	1			R	R			
TBD	2. Materials Meet SMaRT Criteria (Select number of points, up to 5 points)					5		Α	Α	Α	R		
	N. Other 1. Innovation: List innovative measures that meet green building objectives. Enter in the number of points in each category in the blue cells for a maximum of 4 points for the measure. The "points achieved" column will be automatically fill in based on the sum of the points in each category. Points and measures will be evaluated by Build It Green.												
TBD			0	2	2	0	0	Α	Α	Α	R		
TBD	Innovation: Enter up to 4 Points in blue cells at right. Enter description here		0	0	0	0	0	Α	Α	Α	R		
TBD	Innovation: Enter up to 4 Points in blue cells at right. Enter description here		0	0	0	0	0	Α	Α	Α	R		
TBD			0	0	0	0	0	A	Α	Α	R		
TBD Innovation: Enter up to 4 Points in blue cells at right. Enter description here				0	0	0	0	A	Α	Α	R		
Total Available Points in Other: 43+													
Q. California CALGreen CODE			Poir	nts Ava	ilable p	er Mea	sure						
No	Home meets all applicable CALGreen measures listed in above Sections A - P of the GreenPoint Rated checklist.	N	R										
	The following measures are mandatory in the CALGreen code and do not earn points in the GreenPoint Rated Checklist but have been included in the Checklist for the convenience of jurisdictions.												
	The GreenPoint Rater is not a code enforcement official. The measures in this section may be verified by the GreenPoint Rater at their own discretion and/or discretion of the building official.												
Yes	CALGreen 4.106.2 Storm water management during construction.	Υ							R	R	\Box		
Yes	CALGreen 4.106.3 Design for surface water drainage away from buildings.	Υ								R			
Yes	CALGreen 4.303.1 As an alternative to perscriptive compliance, a 20% reduction in baseline water use shall be demonstrated through calculation	Y									R		
Yes	CALGreen 4.406.1 Joints and openings. Annular spaces around pipes, electric cables, conduits, or other openings in plates at exterior walls shall be protected	Y							R				
Yes	CALGreen4.503.1 Gas fireplace shall be a direct-vent sealed-combustion type. Woodstove or pellet stove shall comply with US EPA Phase II emission limits	Y								R	R		
Yes	CALGreen 4.505.2 Vapor retarder and capillary break is installed at slab on grade foundations.							R	R				
Ye® Buil	Yeo Build 7-GGA-Green 4.505.3 19% moisture constant of the included in the constant of the con							Page 13 of 14 R					

The Residences at California Center Pete Kennedy 3685 Planning Scoresheet		Community	Energy	IAQ/Health	Resources	Water	Plan Review	Rough Verification	Final Verification	Documentation
Yes 8. CALGreen 702.1 HVAC system installers are trained and certified in the proper installation of HVAC systems.	Υ									R
Total Available Points in California CALGreen CODE: 0										

Summary

Total Available Points	275+	76	88+	37	83	52	
Minimum Points Required	50	6	30	5	6	3	
Total Points Targeted	97	21	39	10	6	21	

Project Has Met All Minimum Requirements

- Total Project Score of At Least 50 Points
- Required measures:
 - -A2a: 50% waste diversion by weight
 - -E2a: All Shingle Roofing Has 3-Yr Subcontractor Warranty & 20-Yr Manufacturer Warranty
 - -H4a: Compliance with ASHRAE 62.2 Mechanical Ventilation Standards
 - -J1a: 15% above Title 24
 - -N1: Incorporate GreenPoint Rated Checklist in Blueprints
- Minimum points in specific categories:
 - -Community (6 points)
 - -Energy (30 points)
 - -IAQ/Health (5 points)
 - -Resources (6 points)
 - -Water (3 points)
- All Applicable CALGreen Measures in Sections A-P